

CALIFORNIA A500 BC AND A1085 HSS RECTANGLES

SIZE	WALL THICKNESS	LBS./ FT.	20 ft.			24 ft.			40 ft.			48 ft.		
			# OF PCS.	FT. PER BUNDLE	LBS/ BDL	# OF PCS.	FT. PER BUNDLE	LBS/ BDL	# OF PCS.	FT. PER BUNDLE	LBS/ BDL	# OF PCS.	FT. PER BUNDLE	LBS/ BDL
1½ X 3	0.188	4.96	15	300	1488	15	360	1786	15	600	2976	-	-	-
	0.250	6.258	15	300	1877	15	360	2253	15	600	3755	-	-	-
3 X 2	0.083	2.7	42	840	2268	42	1008	2722	-	-	-	-	-	-
	0.120	3.76	42	840	3158	42	1008	3790	30	1200	4512	-	-	-
	0.188	5.59	36	720	4025	36	864	4830	24	960	5366	-	-	-
	0.250	7.1	30	600	4260	25	600	4260	20	800	5680	-	-	-
4 X 2	0.083	3.26	36	720	2347	-	-	-	-	-	-	-	-	-
	0.120	4.57	36	720	3290	36	864	3948	24	960	4387	-	-	-
	0.188	6.86	28	560	3842	28	672	4610	18	720	4939	-	-	-
	0.250	8.8	24	480	4224	24	576	5069	12	480	4224	-	-	-
4 X 3	0.120	5.39	30	600	3234	30	720	3881	24	960	5174	-	-	-
	0.188	8.14	24	480	3907	24	576	4689	18	720	5861	-	-	-
	0.250	10.5	16	320	3360	16	384	4032	12	480	5040	-	-	-
	0.313	12.7	16	320	4064	16	384	4877	12	480	6096	-	-	-
5 X 2	0.120	5.39	24	480	2587	24	576	3105	12	480	2587	-	-	-
	0.188	8.14	24	480	3907	24	576	4689	12	480	3907	-	-	-
	0.250	10.5	16	320	3360	16	384	4032	10	400	4200	-	-	-
5 X 3	0.120	6.21	25	500	3105	25	600	3726	25	1000	6210	25	1200	7452
	0.188	9.41	16	320	3011	16	384	3613	16	640	6022	25	768	11292
	0.250	12.2	12	240	2928	12	288	3514	12	480	5856	12	576	7027
	0.313	14.83	9	180	2669	9	216	3203	9	360	5339	9	432	6407
	0.375	17.27	6	120	2072	6	144	2487	6	240	4145	6	288	4974
	0.500	21.63	4	80	1730	4	96	2076	4	160	3461	4	192	4153
6 X 2	0.083	4.359	24	480	2092	-	-	-	-	-	-	-	-	-
	0.120	6.21	24	480	2981	24	576	3577	12	480	2981	-	-	-
	0.188	9.41	24	480	4517	24	576	5420	12	480	4517	-	-	-

Continued on next page →

CALIFORNIA A500 BC AND A1085 HSS RECTANGLES CON'T.

SIZE	WALL THICKNESS	LBS./ FT.	20 ft.			24 ft.			40 ft.			48 ft.		
			# OF PCS.	FT. PER BUNDLE	LBS/ BDL	# OF PCS.	FT. PER BUNDLE	LBS/ BDL	# OF PCS.	FT. PER BUNDLE	LBS/ BDL	# OF PCS.	FT. PER BUNDLE	LBS/ BDL
6 X 2	0.250	12.2	16	320	3904	16	384	4685	10	400	4880	-	-	-
	0.313	14.83	16	320	4746	16	384	5695	10	400	5932	-	-	-
6 X 3	0.120	7.02	15	300	2106	15	360	2527	15	600	4212	15	720	5054
	0.188	10.03	12	240	2407	12	288	2889	12	480	4814	12	576	5777
	0.250	13.91	9	180	2504	9	216	3005	9	360	5008	9	432	6009
	0.375	19.82	6	120	2378	6	144	2854	6	240	4757	6	288	5708
6 X 4	0.120	7.83	12	240	1879	12	288	2255	12	480	3758	12	576	4510
	0.188	11.97	12	240	2873	12	288	3447	12	480	5746	12	576	6895
	0.250	15.62	9	180	2812	9	216	3374	9	360	5623	9	432	6748
	0.313	19.1	6	120	2292	6	144	2750	6	240	4584	6	288	5501
	0.375	22.4	6	120	2688	6	144	3226	6	240	5376	6	288	6451
7 X 5	0.500	28.43	4	80	2274	4	96	2729	4	160	4549	4	192	5459
	0.188	14.5	9	180	2610	9	192	3132	9	360	5220	9	432	6264
	0.250	19.02	9	180	3424	9	192	4108	9	360	6847	9	432	8217
	0.313	23.32	6	120	2798	6	144	3358	6	240	5597	6	288	6716
	0.375	27.48	6	120	3298	6	144	3957	6	240	6595	6	288	7914
8 X 2	0.500	35.24	4	80	2819	4	96	3383	4	160	5638	-	-	-
	0.120	7.83	10	200	1566	10	240	1879	10	400	3132	10	480	3758
	0.188	11.97	10	200	2394	10	240	2873	10	400	4788	10	480	5746
	0.250	15.62	8	160	2499	8	192	2999	8	320	4998	8	384	5998
8 X 4	0.313	19.1	6	120	2292	6	144	2750	6	240	4584	6	288	5501
	0.188	14.5	8	160	2320	8	192	2784	8	320	4640	8	384	5568
	0.250	19.02	8	160	3043	8	192	3652	8	320	6086	8	384	7304
	0.313	23.32	6	120	2798	6	144	3358	6	240	5597	6	288	6716
	0.375	27.48	4	80	2198	4	96	2638	4	160	4397	4	1920	5276
	0.500	35.24	4	80	2819	4	96	3383	4	160	5638	4	192	6766

* Please inquire with your sales representative on special lengths and packaging