



WYOMING A500 BC AND A1085 HSS RECTANGLES

SIZE	GAUGE	WGT/FT	40 FT.			48 FT.			60 FT.		
			# OF PCS.	FT./BDL	LBS./BDL	# OF PCS.	FT./BDL	LBS./BDL	# OF PCS.	FT./BDL	LBS./BDL
5 × 3	.125	6.46	25	1000	6460	25	1200	7752	10	600	3876
	.188	9.42	16	640	6029	16	768	7235	10	600	5652
	.250	12.21	12	480	5861	12	576	7033	12	720	8791.2
	.313	14.83	9	360	5339	9	432	6407	9	540	8008.2
	.375	17.27	6	240	4145	6	288	4974	6	360	6217.2
	.500	21.63	4	160	3461	4	192	4153	4	240	5191.2
5 × 4	.188	10.70	INQUIRE			INQUIRE			INQUIRE		
	.250	13.91	9	360	5008	9	432	6009	-	-	-
	.375	19.82	6	240	4757	-	-	-	-	-	-
	.500	25.03	6	120	3004	-	-	-	-	-	-
6 × 2	.120	6.21	12	480	2981	12	576	3577	-	-	-
	.188	9.41	12	480	4517	12	576	5420	-	-	-
	.250	12.20	10	400	4880	10	480	5856	-	-	-
6 × 3	.120	7.02	15	600	4212	15	720	5054	15	900	6318
	.188	10.7	12	480	5136	12	576	6163	12	720	7704
	.250	13.91	9	360	5008	9	432	6009	9	540	7511.4
	.313	16.96	6	240	4070	6	288	4884	6	360	6105.6
	.375	19.82	6	240	4757	6	288	5708	6	360	7135.2
	.500	25.03	6	240	6007	6	288	7209	6	360	9010.8
6 × 4	.125	8.16	12	480	3917	12	576	4700	12	720	5875.2
	.188	11.97	12	480	5746	12	576	6895	12	720	8618.4
	.250	15.62	9	360	5623	9	432	6748	9	540	8434.8
	.313	19.08	6	240	4579	6	288	5495	6	360	6868.8
	.375	22.34	6	240	5362	6	288	6434	6	360	8042.4
	.500	28.43	4	160	4549	4	192	5459	4	240	6823.2
7 × 4	.125	-	INQUIRE			INQUIRE			INQUIRE		
	.188	-	INQUIRE			INQUIRE			INQUIRE		
	.250	17.32	8	320	5542	-	-	-	-	-	-
	.313	-	INQUIRE			INQUIRE			INQUIRE		
	.375	24.93	4	160	3989	-	-	-	-	-	-
	.500	-	INQUIRE			INQUIRE			INQUIRE		

Continued on next page →



CALIFORNIA
8901 Arrow Route :: Rancho Cucamonga, CA 91730

WYOMING
5310 Clear Creek Parkway :: Cheyenne, WY 82007

WWW.SEARINGINDUSTRIES.COM

WYOMING A500 BC AND A1085 HSS RECTANGLES CON'T.

SIZE	GAUGE	WGT/FT	40 FT.			48 FT.			60 FT.		
			# OF PCS.	FT./BDL	LBS./BDL	# OF PCS.	FT./BDL	LBS./BDL	# OF PCS.	FT./BDL	LBS./BDL
7 × 5	.125	-	-	0	0	-	-	-	-	-	-
	.188	14.53	8	320	4650	8	384	5580	8	480	6974.4
	.250	19.02	8	320	6086	8	384	7304	8	480	9129.6
	.313	23.32	6	240	5597	6	288	6716	6	360	8395.2
	.375	27.48	4	160	4397	4	192	5276	4	240	6595.2
	.500	35.24	4	160	5638	4	192	6766	4	240	8457.6
8 × 3	.125	9.01	10	400	3604	10	480	4325	10	600	5406
	.188	13.30	10	400	5320	10	480	6384	10	600	7980
	.250	17.32	8	320	5542	8	384	6651	8	480	8313.6
	.313	21.22	8	320	6790	8	384	8148	8	480	10185.6
	.375	24.93	8	320	7978	8	384	9573	8	480	11966.4
8 × 4	.125	9.86	8	320	3155	8	384	3786	8	480	4732.8
	.188	14.53	8	320	4650	8	384	5580	8	480	6974.4
	.250	19.02	8	320	6086	8	384	7304	8	480	9129.6
	.313	23.32	6	240	5597	6	288	6716	6	360	8395.2
	.375	27.48	4	160	4397	4	192	5276	4	240	6595.2
	.500	35.24	4	160	5638	4	192	6766	4	240	8457.6
8 × 6	.125	11.54	6	240	2770	6	288	3324	6	360	4154.4
	.188	17.08	6	240	4099	6	288	4919	6	360	6148.8
	.250	22.42	6	240	5381	6	288	6457	6	360	8071.2
	.313	27.59	6	240	6622	6	288	7946	4	240	6621.6
	.375	32.58	4	160	5213	4	192	6255	4	240	7819.2
	.500	42.05	4	160	6728	4	192	8074	2	120	5046
10 × 4	.188	17.08	8	320	5466	8	384	6559	4	240	4099.2
	.250	22.42	6	240	5381	6	288	6457	4	240	5380.8
	.313	27.59	6	240	6622	6	288	7946	4	240	6621.6
	.375	32.58	4	160	5213	4	192	6255	4	240	7819.2
	.500	42.05	4	160	6728	4	192	8074	4	240	10092

Continued on next page →

WYOMING A500 BC AND A1085 HSS RECTANGLES CON'T.

SIZE	GAUGE	WGT/FT	40 FT.			48 FT.			60 FT.		
			# OF PCS.	FT./BDL	LBS./BDL	# OF PCS.	FT./BDL	LBS./BDL	# OF PCS.	FT./BDL	LBS./BDL
10 × 6	.188	19.63	6	240	4711	6	288	5653	4	240	4711.2
	.250	25.82	6	240	6197	6	288	7436	4	240	6196.8
	.313	31.84	4	160	5094	4	192	6113	4	240	7641.6
	.375	37.69	4	160	6030	4	192	7236	4	240	9045.6
	.500	48.85	4	160	7816	4	192	9379	2	120	5862
10 × 8	.188	22.18	4	160	3549	4	192	4259	4	240	5323.2
	.250	29.23	4	160	4677	4	192	5612	4	240	7015.2
	.313	36.1	4	160	5776	4	192	6931	4	240	8664
	.375	42.79	4	160	6846	4	192	8216	4	240	10269.6
	.500	55.66	4	160	8906	4	192	10687	4	240	13358.4
12 × 4	.188	19.63	4	160	3141	4	192	3769	4	240	4711.2
	.250	25.82	4	160	4131	4	192	4957	4	240	6196.8
	.313	31.84	4	160	5094	4	192	6113	4	240	7641.6
	.375	37.69	4	160	6030	4	192	7236	4	240	9045.6
	.500	48.85	4	160	7816	4	192	9379	2	120	5862
12 × 6	.188	22.18	4	160	3549	4	192	4259	4	240	5323.2
	.250	29.23	4	160	4677	4	192	5612	4	240	7015.2
	.313	36.1	4	160	5776	4	192	6931	4	240	8664
	.375	42.79	4	160	6846	4	192	8216	4	240	10269.6
	.500	55.66	4	160	8906	4	192	10687	4	240	13358.4
12 × 8	.188	24.73	6	240	5935	6	288	7122	4	240	5935.2
	.250	32.63	4	160	5221	4	192	6265	4	240	7831.2
	.313	40.35	4	160	6456	4	192	7747	4	240	9684
	.375	47.90	4	160	7664	4	192	9197	2	120	5748
	.500	62.46	2	80	4997	2	96	5996	2	120	7495.2