

WYOMING A500 BC AND A1085 HSS ROUNDS

PIPE SIZE	OD	SCHEDULE	GAUGE	WGT/FT.	21 FT.		42 FT.	
					PCS.	BDL. WGT	PCS.	BDL. WGT
5"	5.563"	10	.134	7.777	10	1,633	10	3,266
	5.563"	-	.156	9.017	10	1,894	10	3,787
	5.563"	40	.258	14.631	10	3,073	10	6,145
	5.563"	80	.375	20.797	10	4,367	10	8,735
6"	6.625"	10	.134	9.289	7	1,365	7	2,731
	6.625"	-	.156	10.79	7	1,586	7	3,172
	6.625"	20	.188	12.92	7	1,899	7	3,798
	6.625"	30	.250	17.02	7	2,502	7	5,004
	6.625"	40	.280	18.992	7	2,792	7	5,584
	6.625"	80	.432	28.60	7	4,204	7	8,408
	6.625"	-	.500	32.74	7	4,813	7	9,626
8"	8.625"	-	.188	16.96	7	2,493	7	4,986
	8.625"	20	.250	22.36	7	3,287	7	6,574
	8.625"	40	.322	28.58	7	4,201	7	8,403
	8.625"	-	.375	33.04	7	4,857	7	9,714
	8.625"	80	.500	43.428	7	6,384	2	3,648
10"	10.750"	10	.165	18.67	2	784	2	1,568
	10.750"	-	.188	21.23	2	892	2	1,783
	10.750"	20	.250	28.061	2	1,179	2	2,357
	10.750"	40	.365	40.521	2	1,702	2	3,404
	10.750"	-	.375	41.591	2	1,747	2	3,494
	10.750"	60	.500	54.786	2	2,301	2	4,602
12"	12.750"	-	.188	25.25	2	1,061	2	2,121
	12.750"	20	.250	33.406	2	1,403	2	2,806
	12.750"	STD	.375	49.608	2	2,084	2	4,167
	12.750"	40	.406	53.575	2	2,250	2	4,500
	12.750"	EXH	.500	65.476	2	2,750	2	5,500