

WYOMING A500 BC AND A1085 HSS SQUARES

SIZE	GAUGE	WGT/FT.	40 FT.			48 FT.			60 FT.		
			# OF PCS.	FT/BDL	LBS/BDL	# OF PCS.	FT/BDL	LBS/BDL	# OF PCS.	FT/BDL	LBS/BDL
4" SQ.	.125	6.46	25	1000	6460	25	1200	7752	25	1500	9690
	.188	9.42	16	640	6028.8	16	768	7234.56	16	960	9043.2
	.250	12.21	12	480	5860.8	12	576	7032.96	12	720	8791.2
	.313	14.83	9	360	5338.8	9	432	6406.56	9	540	8008.2
	.375	17.27	6	240	4144.8	6	288	4973.76	6	360	6217.2
	.500	21.63	6	240	5191.2	6	288	6229.44	6	360	7786.8
5" SQ.	.125	8.16	12	480	3916.8	12	576	4700.16	12	720	5875.2
	.188	11.97	12	480	5745.6	9	432	5171.04	9	540	6463.8
	.250	15.62	9	360	5623.2	9	432	6747.84	9	540	8434.8
	.313	19.08	6	240	4579.2	6	288	5495.04	6	360	6868.8
	.375	22.34	6	240	5361.6	6	288	6433.92	6	360	8042.4
	.500	28.43	4	160	4548.8	4	192	5458.56	4	240	6823.2
6" SQ.	.125	9.86	9	360	3549.6	9	432	4259.52	9	540	5324.4
	.188	14.53	9	360	5230.8	9	432	6276.96	9	540	7846.2
	.250	19.02	6	240	4564.8	6	288	5477.76	6	360	6847.2
	.313	23.34	6	240	5601.6	6	288	6721.92	6	360	8402.4
	.375	27.48	6	240	6595.2	6	288	7914.24	6	360	9892.8
	.500	35.24	4	160	5638.4	4	192	6766.08	4	240	8457.6
7" SQ.	.125	11.54	6	240	2769.6	6	288	3323.52	6	360	4154.4
	.188	17.08	6	240	4099.2	6	288	4919.04	6	360	6148.8
	.250	22.42	6	240	5380.8	6	288	6456.96	6	360	8071.2
	.313	27.59	6	240	6621.6	6	288	7945.92	6	360	9932.4
	.375	32.58	6	240	7819.2	6	288	9383.04	6	360	11728.8
	.500	42.05	4	160	6728	4	192	8073.6	4	240	10092

Continued on next page →

WYOMING A500 BC AND A1085 HSS SQUARES CON'T.

SIZE	GAUGE	WGT/FT.	40 FT.			48 FT.			60 FT.		
			# OF PCS.	FT/BDL	LBS/BDL	# OF PCS.	FT/BDL	LBS/BDL	# OF PCS.	FT/BDL	LBS/BDL
8" SQ.	.125	13.27	6	240	3184.8	6	288	3821.76	6	360	4777.2
	.188	19.63	6	240	4711.2	6	288	5653.44	6	360	7066.8
	.250	25.82	6	240	6196.8	6	288	7436.16	6	360	9295.2
	.313	31.84	4	160	5094.4	4	192	6113.28	4	240	7641.6
	.375	37.69	4	160	6030.4	4	192	7236.48	4	240	9045.6
	.500	48.85	4	160	7816	4	192	9379.2	2	120	5862
9" SQ.	.125	14.96	4	160	2393.6	4	192	2872.32	4	240	3590.4
	.188	22.18	4	160	3548.8	4	192	4258.56	4	240	5323.2
	.250	29.23	4	160	4676.8	4	192	5612.16	4	240	7015.2
	.313	36.1	4	160	5776	4	192	6931.2	4	240	8664
	.375	42.79	4	160	6846.4	4	192	8215.68	2	120	5134.8
	.500	55.66	2	80	4452.8	2	96	5343.36	2	120	6679.2
10" SQ.	.188	24.73	4	160	3956.8	4	192	4748.16	4	240	5935.2
	.250	32.63	4	160	5220.8	4	192	6264.96	4	240	7831.2
	.313	40.35	4	160	6456	4	192	7747.2	4	240	9684
	.375	47.90	4	160	7664	4	192	9196.8	2	120	5748
	.500	62.46	2	80	4996.8	2	96	5996.16	2	120	7495.2