

| PIPE SIZE | OD | GAUGE | LBS PER FT | 21' PCS | FT PER | LBS | 24' PCS | FT PER | LBS | 42' PCS | FT PER | LBS |
|-----------|-------|-------|------------|---------|--------|------|---------|--------|------|---------|--------|------|
| 1/2" | .840 | 0.109 | 0.850 | 127 | 2667 | 2267 | 127 | 3048 | 2591 | | | |
| 3/4" | 1.050 | 0.113 | 1.131 | 84 | 1764 | 1995 | | | | | | |
| 1" | 1.315 | 0.133 | 1.68 | 60 | 1260 | 2117 | 60 | 1440 | 2419 | | | |
| 1 1/4" | 1.66 | 0.109 | 1.805 | 44 | 924 | 1668 | 44 | 1056 | 1906 | | | |
| 1 1/4" | 1.66 | 0.140 | 2.273 | 44 | 924 | 2100 | 44 | 1056 | 2400 | | | |
| 1 1/2" | 1.9 | 0.109 | 2.085 | 37 | 777 | 1620 | 37 | 888 | 1851 | | | |
| 1 1/2" | 1.9 | 0.145 | 2.718 | 37 | 777 | 2112 | 37 | 888 | 2414 | | | |
| 1 1/2" | 1.9 | 0.200 | 3.631 | 37 | 777 | 2822 | | | | | | |
| 2" | 2.375 | 0.109 | 2.638 | 29 | 609 | 1607 | | | | | | |
| 2" | 2.375 | 0.154 | 3.653 | 29 | 609 | 2225 | 29 | 696 | 2542 | 29 | 1218 | 4449 |
| 2" | 2.375 | 0.218 | 5.022 | 19 | 399 | 2004 | | | | 19 | 798 | 4008 |
| 2 1/2" | 2.875 | 0.120 | 3.531 | 19 | 399 | 1409 | | | | | | |
| 2 1/2" | 2.875 | 0.203 | 5.79 | 19 | 399 | 2310 | | | | 19 | 798 | 4620 |
| 3" | 3.5 | 0.216 | 7.58 | 19 | 399 | 3024 | | | | 19 | 798 | 6049 |
| 3 1/2" | 4.0 | 0.120 | 4.97 | 10 | 210 | 1044 | | | | 10 | 420 | 2087 |
| 3 1/2" | 4.0 | 0.226 | 9.11 | 10 | 210 | 1913 | | | | 10 | 420 | 3826 |
| 4" | 4.5 | 0.120 | 5.61 | 10 | 210 | 1178 | | | | 10 | 420 | 2356 |
| 4" | 4.5 | 0.237 | 10.79 | 10 | 210 | 2266 | | | | 10 | 420 | 4532 |
| 4" | 4.5 | 0.337 | 14.98 | 7 | 147 | 2202 | | | | 7 | 294 | 4404 |
| 6" | 6.625 | 0.134 | 9.289 | 7 | 147 | 1365 | | | | 7 | 294 | 2731 |
| 6" | 6.625 | 0.188 | 12.92 | 7 | 147 | 1899 | | | | 7 | 294 | 3798 |
| 6" | 6.625 | 0.250 | 17.02 | 7 | 147 | 2502 | | | | 7 | 294 | 5004 |
| 6" | 6.625 | 0.280 | 18.992 | 7 | 147 | 2792 | | | | 7 | 294 | 5584 |
| 6" | 6.625 | 0.432 | 28.6 | 3 | 63 | 1800 | | | | 3 | 126 | 3600 |