

STRUCTURAL STEEL TUBING

Solid Metal

Melting Point:
2750° F

Appearance:
Grey-Black

Odor:
None

Specific Gravity (H₂O=1):
Greater than 7

TYPICAL CHEMICAL COMPOSITION & HAZARD DATA

Ingredient	CAS #	Weight %	Hazard Data (1984 TLV's)
Iron	7439-89-6	Balance	5mg/M_for iron oxides fumes
Carbon	7440-44-0		Not listed
Manganese	7439-96-5	1.7 max	5mg/M_fumes & dust
Phosphorus	7723-14-0	.15 max	None for inorganic phosphates
Sulfur	7704-34-9	.35 max	5mg/M_as SO ₂
Columbium	7440-25-7	.10 max	None established
Vanadium	7440-62-2	.20 max	.005mg/M_Al metal & oxide
Aluminum	7429-90-5	.10 max	10 mg/M_Al metal & oxide
Copper	7440-50-8	.20 - 0.6	0.2 mg/M_Copper fume 1 mg/M_Copper dust

HEALTH HAZARD DATA

Steel products under normal conditions do not present a health hazard. However, when subjected to welding, burning, grinding, abrasive blasting, heat treatment, pickling or similar operations, potentially hazardous fumes or dusts may be emitted.

Primary Route of Entry	Inhalation
Health Hazards	Iron (iron oxide): Irritation of eyes, nose, throat Metallic taste in mouth or metal fume fever
Effects of Exposure	Iron (iron oxide): Pulmonary (upper respiratory) effects, siderosis. Manganese: pneumonitis, bronchitis, lack of coordination
Carcinogenic Hazard	Not considered to be carcinogenic
Emergency and First Aid Procedures	In the event of exposure to high concentrations of metal fumes, remove person to fresh air, administer oxygen and seek prompt medical attention

FIRE AND EXPLOSION DATA	
Flash Point:	N/A
Extinguishing Media:	Use methods applicable to surrounding area
Flammable Limits:	N/A
Unusual Fire & Explosion Hazards:	NONE
Special Fire Fighting Procedures:	N/A

REACTIVITY DATA

Steel is considered stable under normal circumstances. Will react with strong acid. At elevated temperatures, it may liberate metal fumes, iron oxides and oxides of other alloying elements.

SPECIAL PROTECTION INFORMATION

Steel is considered stable under normal circumstances. Will react with strong acid. At elevated temperatures, it may liberate metal fumes, iron oxides and oxides of other alloying elements.

WASTE DISPOSAL METHODS

Disposal of in accordance with Federal, State and/or local waste regulations.

OTHER INFORMATION

Castrol Fluidform 107 used as coolant during manufacturing of structural steel tubing.

As of Jan. 2016

The information contained in the Material Safety Data Sheet is believed to be correct, but Searing Industries makes no representations, guarantees or warranties of any kind as to its absolute accuracy.

SEARING INDUSTRIES MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY, ANY IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE AND ANY IMPLIED WARRANTIES OTHERWISE ARISING FROM COURSE OF DEALING OR TRADING.

