

PIPE SIZE	SCHED.	MILL	OD	GAUGE	WGT/FT.	21 FT.			24 FT.			42 FT.		
						PCS.	FT PER	LBS	PCS.	FT PER	LBS	PCS.	FT PER	LBS
1/2"	40	CA	0.84"	0.109	0.85	127	2667	2267						
3/4"	40	CA	1.050"	0.113	1.131	84	1764	1,995						
1"	10	CA	1.315"	0.109	1.4	60	1260	1764	60	1440	2016			
	40	CA	1.315"	0.133	1.68	60	1260	2117	60	1440	2419			
1 1/4"	10	CA/WY	1.66"	0.109	1.805	44	924	1668	44	1056	1906			
	40	CA/WY	1.66"	0.140	2.273	44	924	2100	44	1056	2400			
1 1/2"	10	CA/WY	1.9"	0.109	2.085	37	777	1620	37	888	1851			
	40	CA/WY	1.9"	0.145	2.718	37	777	2112	37	888	2414			
	80	CA/WY	1.9"	0.200	3.631	37	777	2822	37	888	3224			
2"	10	CA/WY	2.375"	0.109	2.638	29	609	1607	29	696	1836			
	40	CA/WY	2.375"	0.154	3.653	29	609	2225	29	696	2542	29	1218	4449
	80	CA/WY	2.375"	0.218	5.022	29	399	3058	29	696	3495	29	798	6117
2 1/2"	10	CA/WY	2.875"	0.120	3.531	19	399	1409	19	456	1609	19	798	2290
	40	CA/WY	2.875"	0.203	5.79	19	399	2310	19	456	2640	19	798	4620
3"	40	CA/WY	3.5"	0.216	7.58	19	399	3024	19	456	3456	19	798	6049
3 1/2"	10	CA/WY	4"	0.120	4.977	10	210	1045	10	240	1192	10	420	2090
	40	CA/WY	4"	0.226	9.11	10	210	1913	10	240	2186	10	420	3826
4"	10	CA/WY	4.5"	0.120	5.61	10	210	1178	10	240	1346	10	420	2356
	40	CA/WY	4.5"	0.237	10.79	10	210	2266	10	240	2589	10	420	4532
	80	CA	4.5"	0.337	14.98	7	147	2202	7	168	2516	7	294	4404
5"	10	WY	5.563"	0.134	7.777	10	210	1,633	10	240	1864	10	420	3,266
		WY	5.563"	0.156	9.017	10	210	1,894	10	240	2162	10	420	3,787
	40	WY	5.563"	0.258	14.631	10	210	3,073	10	240	3511	10	420	6,145
	80	WY	5.563"	0.375	20.797	10	210	4,367	10	240	4989	10	420	8,735

Continued on next page →

PIPE SIZE	SCHED.	MILL	OD	GAUGE	WGT/FT.	21 FT.			24 FT.			42 FT.		
						PCS.	FT PER	LBS	PCS.	FT PER	LBS	PCS.	FT PER	LBS
6"	10	CA/WY	6.625"	0.134	9.289	7	147	1365	7	168	1559	7	294	2731
		CA/WY	6.625"	0.188	12.92	7	147	1899	7	168	2170	7	294	3798
		CA/WY	6.625"	0.250	17.02	7	147	2502	7	168	2859	7	294	5004
	40	CA/WY	6.625"	0.280	18.992	7	147	2792	7	168	3190	7	294	5584
	80	CA/WY	6.625"	0.432	28.6	3	63	1800	3	72	2059	3	126	3600
8"		WY	6.625"	0.500	32.74	7	147	4,813	7	168	5,500	7	294	9,626
		WY	8.625"	0.188	16.96	7	147	2,493	7	168	2,849	7	294	4,986
	20	WY	8.625"	0.250	22.36	7	147	3,287	7	168	3,756	7	294	6,574
	40	WY	8.625"	0.322	28.58	7	147	4,201	7	168	4,801	7	294	8,403
		WY	8.625"	0.375	33.04	7	147	4,857	7	168	5,550	7	294	9,714
10"	80	WY	8.625"	0.500	43.428	7	147	6,384	7	168	7,294	2	84	3,648
	10	WY	10.750"	0.165	18.67	2	42	784	2	48	896	2	84	1,568
		WY	10.750"	0.188	21.23	2	42	892	2	48	1,019	2	84	1,783
	20	WY	10.750"	0.250	28.061	2	42	1,179	2	48	1,346	2	84	2,357
	40	WY	10.750"	0.365	40.521	2	42	1,702	2	48	1,944	2	84	3,404
		WY	10.750"	0.375	41.591	2	42	1,747	2	48	1,996	2	84	3,494
12"	60	WY	10.750"	0.500	54.786	2	42	2,301	2	48	2,629	2	84	4,602
		WY	12.750"	0.188	25.25	2	42	1,061	2	48	1,212	2	84	2,121
	20	WY	12.750"	0.250	33.406	2	42	1,403	2	48	1,603	2	84	2,806
	STD	WY	12.750"	0.375	49.608	2	42	2,084	2	48	2,380	2	84	4,167
	40	WY	12.750"	0.406	53.575	2	42	2,250	2	48	2,571	2	84	4,500
	EXH	WY	12.750"	0.500	65.476	2	42	2,750	2	48	3,142	2	84	5,500