

PIPE SIZE	SCHED.	MILL	OD	WALL THICKNESS	LBS./FT.	21 FT.			24 FT.			42 FT.		
						# OF PCS.	FT. PER BUNDLE	LBS/BDL	# OF PCS.	FT. PER BUNDLE	LBS/BDL	# OF PCS.	FT. PER BUNDLE	LBS/BDL
1/2"	40	CA	0.840"	0.109	0.85	127	2667	2267						
3/4"	40	CA	1.050"	0.113	1.131	84	1764	1995	84	2016	2280			
1"	10	CA	1.315"	0.109	1.4	61	1260	1793	61	1440	5040			
	40	CA	1.315"	0.133	1.68	61	1260	2152	61	1440	2460			
1 1/4"	10	CA/WY	1.660"	0.109	1.805	44	924	1668	44	1056	1906			
	40	CA/WY	1.660"	0.140	2.273	44	924	2100	44	1056	2400			
1 1/2"	10	CA/WY	1.900"	0.109	2.085	37	777	1620	37	888	1851			
	40	CA/WY	1.900"	0.145	2.718	37	777	2112	37	888	2414			
	80	CA/WY	1.900"	0.200	3.631	37	777	2822	37	888	3224			
2"	10	CA/WY	2.375"	0.109	2.638	29	609	1607	29	696	1836			
	40	CA/WY	2.375"	0.154	3.653	29	609	2225	29	696	2542	29	1218	4449
	80	CA/WY	2.375"	0.218	5.022	29	399	3058	29	696	3495	29	798	6117
2 1/2"	10	CA/WY	2.875"	0.120	3.531	19	399	1409	19	456	1609	19	798	2290
	40	CA/WY	2.875"	0.203	5.79	19	399	2310	19	456	2640	19	798	4620
3"	40	CA/WY	3.5"	0.216	7.58	19	399	3024	19	456	3456	19	798	6049
3 1/2"	10	CA/WY	4"	0.120	4.977	10	210	1045	10	240	1192	10	420	2090
	40	CA/WY	4"	0.226	9.11	10	210	1913	10	240	2186	10	420	3826
4"	10	CA/WY	4.5"	0.120	5.61	10	210	1178	10	240	1346	10	420	2356
	40	CA/WY	4.5"	0.237	10.79	10	210	2266	10	240	2589	10	420	4532
	80	CA	4.5"	0.337	14.98	7	147	2202	7	168	2516	7	294	4404
5"	10	WY	5.563"	0.134	7.777	10	210	1633	10	240	1864	10	420	3266
		WY	5.563"	0.156	9.017	10	210	1894	10	240	2162	10	420	3787
	40	WY	5.563"	0.258	14.631	10	210	3073	10	240	3511	10	420	6145
	80	WY	5.563"	0.375	20.797	10	210	4367	10	240	4989	10	420	8735
		WY	5.563"	0.500	27.06	7	147	3978	7	168	4546	7	294	7956

Continued on next page →

PIPE SIZE	SCHED.	MILL	OD	WALL THICKNESS	LBS./FT.	21 FT.			24 FT.			42 FT.		
						# OF PCS.	FT. PER BUNDLE	LBS/BDL	# OF PCS.	FT. PER BUNDLE	LBS/BDL	# OF PCS.	FT. PER BUNDLE	LBS/BDL
6"	10	CA/WY	6.625"	0.134	9.289	7	147	1365	7	168	1559	7	294	2731
		CA/WY	6.625"	0.188	12.92	7	147	1899	7	168	2170	7	294	3798
		CA/WY	6.625"	0.250	17.02	7	147	2502	7	168	2859	7	295	5004
	40	CA/WY	6.625"	0.280	18.992	7	147	2792	7	168	3190	7	294	5584
	80	CA/WY	6.625"	0.432	28.6	3	63	1800	3	72	2059	3	126	3600
		WY	6.625"	0.500	32.74	7	147	4813	7	168	5500	7	294	9626
8"		WY	8.625"	0.188	16.96	7	147	2493	7	168	2849	7	294	4986
	20	WY	8.625"	0.250	22.36	7	147	3287	7	168	3756	7	294	6574
	40	WY	8.625"	0.322	28.58	7	147	4201	7	168	4801	7	294	8403
		WY	8.625"	0.375	33.04	7	147	4857	7	168	5550	7	294	9714
		WY	8.625"	0.406	35.64	7	147	5329	7	168	5988	7	294	10478
	80	WY	8.625"	0.500	43.428	2	147	6384	2	168	7294	2	84	3648
10"	10	WY	10.750"	0.165	18.67	2	42	784	2	48	896	2	84	1568
		WY	10.750"	0.188	21.23	2	42	892	2	48	1019	2	84	1783
	20	WY	10.750"	0.250	28.061	2	42	1179	2	48	1346	2	84	2357
	40	WY	10.750"	0.365	40.521	2	42	1702	2	48	1944	2	84	3404
		WY	10.750"	0.375	41.591	2	42	1747	2	48	1996	2	84	3494
	60	WY	10.750"	0.500	54.786	2	42	2301	2	48	2629	2	84	4602
12"		WY	12.750"	0.188	25.25	2	42	1061	2	48	1212	2	84	2121
	20	WY	12.750"	0.250	33.406	2	42	1403	2	48	1603	2	84	2806
	STD	WY	12.750"	0.375	49.608	2	42	2084	2	48	2380	2	84	4167
	40	WY	12.750"	0.406	53.575	2	42	2250	2	48	2571	2	84	4500
	EXH	WY	12.750"	0.500	65.476	2	42	2750	2	48	3142	2	84	5500